



# ELITE

WOODWORKING MACHINERY

<b>Product name:</b>	LP163/93
<b>Area of application:</b>	before buffing wheels /surface scraper (edgebanding )
<b>Application:</b>	Spray onto the upper and lower edge area of the workpiece →Removal of release agent and loose glue residue →Cooling of the edgeband and glue joint →Matt radius of the machined edgeband re-matches the surface finish

### Physical and chemical characteristics:

- Form: Fluid
- Colour: Red
- Smell: Characteristic
- Ignition temperature: 425 °C  
Product is not selfigniting.
- Boiling range: > 65 °C
- Flash point: < 21 °C
- Values for explosion: Lower 3,5 Vol %  
Upper 15,0 Vol %  
Product is not explosive.  
(formation of explosive air/steam mixtures is possible)
- Density: 0,81 g/cm<sup>3</sup> (at 20°C)

**Composition:** Mixture of ethanol

**Available packaging (liter):** 30|200|1000

### Safety Instructions:

- Transport: Class 3, PG II
- Customs tariffe : 38140090
- Storage: Keep container tightly closed. Store in a cool, dry place.
- Shelf life: Unlimited shelf life when stored properly
- Disposal: According to official regulations, or returnable packaging

- ✓ Low consumption: <1 litre per fine nozzle per 5000 running metres
- ✓ Compatible with all commercially available edge bands and adhesives
- ✓ Finish Quality
- ✓ High-quality raw materials
- ✓ Not harmful to the environment or health



Unit 5, Tudor Lodge, Powerstown Road, Clonee, Dublin 15, D15 AXF4

PHONE 01 699 1516

[www.elitewoodworkingmachinery.ie](http://www.elitewoodworkingmachinery.ie)