



ELITE

WOODWORKING MACHINERY

Product name: LP305/98

Application: Manual cleaning of plastic surfaces.
→Effortlessly removes glue residues

Physical and chemical characteristics:

- Form: Fluid
- Colour: Colourless
- Smell: Characteristic
- Ignition temperature: Not determined
Product is not selfigniting.
- Boiling range: > 78 °C
- Flash point: ~ 1 °C
- Values for explosion: Lower 0,7 Vol %
Upper (lowest and highest value of the individual components)
Product is not explosive.
(formation of explosive air/steam mixtures is possible)
- Density: 0,753 g/cm³ (at 20°C)
- Vapour pressure: 57 hPa (at 20°C)

Composition: Mixture of hydrocarbons and ethanol

Available packaging (liter): 1|30|200|1000

Safety Instructions:

- Transport: Class 3, PG II
- Customs tariffe : 34029090
- Storage: Keep container tightly closed. Store in a cool, dry place.
- Shelf life: Unlimited shelf life when stored properly
- Disposal: According to official regulations, or returnable packaging

- ✓ Strong cleaning power
- ✓ Quick drying
- ✓ Residue free evaporation
- ✓ Low odour
- ✓ Hexane free
- ✓ Benzene free



Unit 5, Tudor Lodge, Powerstown Road, Clonee, Dublin 15, D15 AXF4

PHONE 01 699 1516

www.elitewoodworkingmachinery.ie