



ELITE

WOODWORKING MACHINERY

Product name:	LPZ/II
Area of application:	Before pre-milling (edgebanding)
Application:	Spray onto the upper and lower edge area of the workpiece. Prevents the adhesion of emerging glue onto the workpiece.

Physical and chemical characteristics:

- Form: Liquid
- Colour: Colourless
- Smell: Alcohol-like
- Ignition temperature: 425 °C
Product is not selfigniting.
- Melting point: -100 °C
- Boiling range: ≥ 78 °C
- Flash point: ~13 °C
- Values for explosion: Lower 3,5 Vol %
Upper 15,0 Vol %
Product is not explosive.
(formation of explosive air/steam mixtures is possible)
- Density: ~ 0,79 g/cm³ (at 20°C)
- Vapour pressure: 59 hPa (at 20°C)
- VOC: 96% volatile organic compounds

Composition: Mixture of ethanol

Available packaging (liter): 30|200|1000

Safety Instructions:

- Transport: Class 3, PG II
 - Customs tariffe : 38140090
 - Storage: Keep container tightly closed. Store in a cool, dry place.
 - Shelf life: Unlimited shelf life when stored properly
 - Disposal: According to official regulations, or returnable packaging
-
- ✓ Low consumption: <1 litre per fine nozzle per 5000 running metres
 - ✓ Compatible with all commercially available edge bands and adhesives
 - ✓ Finish Quality
 - ✓ High-quality raw materials
 - ✓ Not harmful to the environment or health



Unit 5, Tudor Lodge, Powerstown Road, Clonee, Dublin 15, D15 AXF4

PHONE 01 699 1516

www.elitewoodworkingmachinery.ie