



ELITE

WOODWORKING MACHINERY

Product name:	NFLY
Area of application:	Diverse (edgebanding)
Application:	(a) Intermittent application to the pressure roller → Glue residues cannot adhere to the rollers (b) Sprayed edge/protective foil automatically transfers the release agent to the slide shoes → Glue residues do not adhere • Prevents marking and friction (c) Spray directly onto the surface of the edgeband → Avoidance of marking and damage → Protective film is protected and not removed from the edge (d) Direct application onto the DUO scraper → No glogging of the DUO scraper (e) Application to the tooling → Prevents fouling of the trimmers

Physical and chemical characteristics:

- Form: Liquid
- Colour: Green
- Smell: Alcohol-like
- Ignition temperature: 425 °C
Product is not selfigniting.
- Melting point: ~ - 40 °C
- Boiling range: ~ 82 °C
- Flash point: 25 °C
- Values for explosion: Lower 3,5 Vol %
Upper 15,0 Vol %
Product is not explosive.
(formation of explosive air/steam mixtures is possible)
- Density: 0,92 g/cm³ (at 20°C)
- Vapour pressure: 59 hPa (at 20°C)
- VOC: 49,4% volatile organic compounds

Composition: Mixture of ethanol

Available packaging (liter): 30|200|1000

Safety Instructions:

- Transport: Class 3, PG III
- Customs tariffe : 38140090
- Storage: Keep container tightly closed. Store in a cool, dry place.
- Shelf life: Unlimited shelf life when stored properly
- Disposal: According to official regulations, or returnable packaging



Unit 5, Tudor Lodge, Powerstown Road, Clonee, Dublin 15, D15 AXF4

PHONE 01 699 1516

www.elitewoodworkingmachinery.ie